

MINIMUM SPECIFICATIONS FOR (4) FOUR TANDEM AXLE TRUCKS

It is the intent and purpose of these specifications to describe the minimum requirements for (4) four Tandem Axle Trucks to be equipped (by body builder) with a pusher axle or underbody blade, 17 foot asphalt dump body, front mounted plow, wing and rear sander.

These specifications are not meant to be restrictive in any way, but are intended to assure that all proposals submitted for consideration will cover machines of similar design and capacity. In order to evaluate each quotation, this form must be completed in its entirety and returned along with manufacturer's specifications.

The trucks to be furnished must be currently in production, 2022 Model, and shall be manufacturer's standard model, complete with all standard equipment.

	MINIMUM SPECIFICATIONS	SPECIFICATIONS FURNISHED
SIZE:	66,000 lb. GVW	
	150 inches cab (clear) to center of rear axles	
	56 inches center of rear axle spacing to end of frame	
ENGINE:	Diesel, 13 liter or larger, current year EPA emissions compliant	
	450 horsepower, 1700 ft./lbs. torque with engine compression brake, electronic activated	
	Variable clutch fan	
	18 C.F.M. water cooled air compressor	
	Fuel heater/water separator	
	Single vertical exhaust with heat shield and elbow at outlet	
	Under the cab Diesel Particulate Filter (20 inch ground clearance)	
	Automatic with manual override of D.P.F. regeneration	
	Exhaust to be compatible with underbody blade or push axle and plow wing installation	
	Driver controlled inside/outside engine air intake or left side air intake	
	Provision for front P.T.O. no hole in radiator preferred (specify)	
DRIVE TRAIN:	Transmission, Allison automatic, 4500 RDS, 6 speed, on/off hwy, with Transynd synthetic lube and a dash mounted push button shift selector	
	Rear axle, 46,000 lb. capacity with gear ratio for 73 MPH at maximum governor engine RPM	
	Driveline, 1810 series or equivalent	
	Driver controlled differential lock and inter axle full lock	
CHASSIS:	Front axle and springs 20,000 lb. capacity	
	Front axle set back preferred	
	Factory installed right front airbag assist or spring build up for wing plow	
	Rear suspension, 46,000 lb. capacity, Hendrickson HMX-460 series, 54 inch axle center	
	Frame, 3,200,000 RBM with integral front frame extension (no bolt on) to accommodate direct drive pump and front P.T.O. provisions	

MINIMUM	SPECIFICATIONS
----------------	-----------------------

Dual sun visors and roof mounted console with pocket to mount two way radio	
Exterior sun visor over windshield	
Rubber floor mat	
Dual outside heated West Coast style stainless steel mirrors, with 8-7/8 convex below also heated	
Dual air horns with snow shields, single base	
Grab handles, both sides of cab exterior	
Drip rails over doors	
Rubber extensions on front fender wheel openings, 2 inch minimum width	
Extra wide lower non-slip step on left side	
Painted white, base coat/clear coat	
MISCELLANEOUS: All safety equipment required by law	
Engine warranty, including injectors, turbo, water pump and After treatment system. 5Year 200,000 mi. minimum	
Transmission and Drive Line warranty, 3 year 200,000 mile minimum	
Cab rust-through and structure warranty, 5 year minimum	
Towing coverage to dealer for warranty repairs, first 12 months	
Line setting sheets for all components	
One complete set of service and parts manuals and engine manufacturer's service and parts manual, all in book form	
Three sets of keys for each truck	
Fire extinguisher, 5 lb. mounted and triangle kit	
Dealer is responsible for transporting trucks to the truck equipment company designated by the County, within two weeks of arrival at the Dealer	
All warranty start dates shall be day unit placed in service	

TOTAL COST INCLUDING FREIGHT \$ _____

OPTIONS: **Heated Windshield** \$ _____

7 year, 300,000 mile engine warranty including injectors, turbo, water pump and After treatment with zero deductible: \$ _____

5 year, 300,000 mile transmission and driveline warranty: \$ _____

COST OF EXTENDED WARRANTIES: \$ _____

FINAL COST WITH WARRANTIES: \$ _____

Value allowed for trade-in of #171 Tri-Axle plow truck.
 2015 International 7600 with a 12 ltr. engine,(430hp), 4500RDS Allison transmission.
 Full locking rear differentials and Engine Brake.

**Truck has a 17ft. Dump Box, 12ft Front plow, 9ft. Front mounted wing and
Stainless Rear Sander with Spinner: \$ _____**

GAURANTEED DELIVERY DATE: _____

**Dunn County Highway Committee reserves the right to accept or reject the
allowed trade-in value on the purchase of the new trucks. The new trucks
may be purchased without trading in the above trucks.**

**Truck can be viewed by appointment at the Menomonie shop,
680 Stokke PKW Menomonie WI 54751 715-232-2361- Danny Nelson**